



STANDARD FLEXI BLOCK FERRULE SIZES FOR COPPER PIPE			
PIPE SIZE	25mm INSULATION ID x OD	38mm INSULATION ID x OD	50mm INSULATION ID x OD
15cu	12.7 x 64mm	12.7 x 89mm	12.7 x 114mm
20cu	19.0 x 76mm	19.0 x 100mm	19.0 x 127mm
25cu	25.4 x 70mm	25.4 x 102mm	25.4 x 127mm
32cu	31.8 x 83mm	31.8 x 114mm	31.8 x 140mm
40cu	38.1 x 89mm	38.1 x 114mm	38.1 x 140mm
50cu	51.2 x 102mm	51.2 x 127mm	51.2 x 152mm
65cu	63.5 x 114mm	63.5 x 140mm	63.5 x 165mm
80cu	76.2 x 126mm	76.2 x 152mm	76.2 x 178mm
100cu	101.6 x 152mm	101.6 x 178mm	101.6 x 203mm
125cu	127.0 x 177mm	127.0 x 203mm	127.0 x 228mm
150cu	152.4 x 203mm	152.4 x 228mm	152.4 x 252mm
200cu	203.2 x 252mm	203.2 x 275mm	203.2 x 302mm

MATERIAL:	CROSSLINKED CLOSED CELL PE FOAM
DENSITY:	300 kg/m²
MOISTURE ABSORPTION: (BY WEIGHT, ROOM TEMP, 5HRS)	<1%
TENSILE STRENGTH:	2.4 kg/m²
TEAR STRENGTH:	8.3 kg/m²
THERMAL CONDUCTIVITY (ISO8302-1991)	0.065 W/mK
CONSTANT WORKING TEMP	-40°C TO 105°C
COMPRESSIVE STRENGTH JIS 6767	3.4 kg/cm²

COMES BOUND WITH FIRE RATED SILVER SISAL
STANDARD SIZES ONLY: OTHER SIZES AVAILABLE ON REQUEST



STANDARD FLEXI BLOCK FERRULE SIZES FOR STEEL PIPE

PIPE SIZE	25mm INSULATION ID x OD	38mm INSULATION ID x OD	50mm INSULATION ID x OD
15nb	21.3 x 73mm	21.3 x 102mm	21.3 x 127mm
20nb	26.7 x 76mm	26.7 x 102mm	26.7 x 127mm
25nb	33.4 x 83mm	33.4 x 115mm	33.4 x 140mm
32nb	42.2 x 89mm	42.2 x 115mm	42.2 x 140mm
40nb	48.3 x 102mm	48.3 x 127mm	48.3 x 152mm
50nb	60.3 x 115mm	60.3 x 140mm	60.3 x 165mm
65nb	73 x 127mm	73 x 152mm	73 x 178mm
80nb	88.9 x 140mm	88.9 x 165mm	88.9 x 190mm
100nb	114.3 x 165mm	114.3 x 190mm	114.3 x 220mm
125nb	141.3 x 190mm	141.3 x 220mm	141.3 x 240mm
150nb	165.1 x 220mm	165.1 x 240mm	165.1 x 268mm
150nb (sched 40)	168.3 x 220mm	168.3 x 240mm	168.3 x 268mm
200nb	219.1 x 275mm	219.1 x 302mm	219.1 x 324mm
250nb	273.0 x 324mm	273.0 x 356mm	273.0 x 375mm

**COMES BOUND WITH FIRE RATED SILVER SISAL
STANDARD SIZES ONLY: OTHER SIZES AVAILABLE ON REQUEST**

